
ISWL-F11**


Explosion-proof LED Lighting Fixture
ISWL-F11 series for Hazardous Location



Protection Grade
Ex d ⅡC T6 IP66 for Zone 1·2

Drawing





Standard Material

- **Main Body :** Die-Cast Aluminium Alloy
- **Holder :** Die-Cast Aluminium Alloy
- **Glass :** Heat Resistant Hard Glass
- **Bolt & Washer :** Stainless Steel

Standard Color

- Munsell no. 7.5BG 6/1.5
  If you want other color, contact us please.


Technical Data

- **Rated Voltage :** AC 100~240V Below
- **Rated Wattage :** 30W/55W/80W
- **Rated Frequency :** 50Hz/60Hz
- **Entry Size :** 3/4"(22C), 1"(28C)
- **Option** : Receptacle Plug (방폭 or 비방폭)
- **Tamb** : -20°C ≤ Ta ≤ +40°C

Weight

5.8kg

Light Distribution Curve



Ordering Number

Lamp	Watt	Cable 길이 (기본 10m)		
		10m	20m	30m
LED	30W	ISWL-F1130-10m	ISWL-F1130-20m	ISWL-F1130-30m
LED	55W	ISWL-F1155-10m	ISWL-F1155-20m	ISWL-F1155-30m
LED	80W	ISWL-F1180-10m	ISWL-F1180-20m	ISWL-F1180-30m